

HECbox



Battery charger
RP-DC80
multifunctional digital intelligent
battery charger / power supply



LARGE 1.6 INCH LCD DISPLAY SCREEN

A large 1.6-inch LCD Back lite Display screen provides clear accurate and precise display of Charging Status, Charging Voltage, USB output, and DC Voltage Output. With implemented dual Color backlight, the readout function is enabled in the dark.



BACKLIGHT DUAL COLOR

Gives you instant optical view on charger status

With implemented Dual Color backlight in the large LCD screen, RED and BLUE, the readout function is enabled in the dark, that give you clear possibility to use this charger at any place and any time.



BATTERY CHARGING MODE

The RP-DC80 can be used as the Battery Charger. Depending on the mode you wish to use(Battery Charging 16.8V, 2.3A) you need to choose the appropriate extension cable which enables the wished mode.



POWERING PROFESSIONAL CAMCORDER

The RP-DC80 can be used as the Constant Power Supply unit, for all ENG Camcorders. Depending on the mode you wish to use (Constant Power Supply 90W Max) you need to choose the appropriate extension cable which enables the wished mode.

SOUND DEVICE POWERING

The RP-DC80 can be used as the Constant Power Supply unit, for all Sound Device products. Depending on the mode you wish to use (Constant Power Supply 90W Max) you need to choose the appropriate extension cable which enables the wished mode.



STUDIO ENG CAMCORDERS POWER SUPPLY

The RP-DC80 can be used as the Constant Power Supply unit for studio ENG Camcorders application. Depending on the mode you wish to use (Constant Power Supply 90W Max) you need to choose the appropriate extension cable which enables the wished mode.



POWERING THE LED PANEL



Tech Specification

Charger Model : RP-DC80 Intelligent Professional Multi Purpose Digital Battery Charger/Power Supply

Power Requirements AC : AC 110-240 V , 50/60 Hz

Power Consumption : Max 100W

Power Output 1 : DC 12.5V , 5A / 90W (max)

Power Output 2 : DC 17V , 5A / 90W (max)

Charger Output : DC 16.8V 2.3A

USB Power Output : DC 5V 1A / 5W (max)

Operation Control : 1.6-inch LCD Back lite Display Dual Color – Shows Charging Status / Voltage of DC and USB out

Operating Temperature : -10 to 40 C

Dimensions (WxDxH) : 132 x 58 x 30 mm

Weight (Gram,Pound,Ounce) : 365g

Operational Method : RP-DC80 use optional Extension Power/Charger Cables (sold separately) according to the wished mode



RPC-XY / HR10A-7P-4P
4-pin Plug

RPC-DT / D-Tap Plug

RPC-4X / 4-pin XLR Plug

RPC-SO / C-PIN
5.5mm Angle Plug

RPC-DTP / D-Tap
Plug

HedBox

Copyright HedBox 2018. All rights reserved.
All trademarks are property of their respective owners.
www.hed-box.com