

# **UNIX-1BL**

HEDBOX UNIX-1BL V-LOCK MOUNT PROFESSIONAL CINE BATTERY PLATE WITH 3X D-TAP (14.8V/10A) + 1 X USB (5.1V/2.1A) AND 1X BREAKAWAY 50CM CABLE 2-PIN PUSH PULL FHG.1B.302 MALE RIGHT ANGLE CONNECTOR

#### **OVERVIEW:**

Hedbox UNIX-1BL V-Lock Mount Professional Cine Battery Plate with 1 x USB (5.1V/2.1A) + 3x D-Tap (14.8V/10A) and 1x Breakaway 50cm Cable with 2-pin Push Pull FHG.1B.302 Male Right Angle Connector.

UNIX Professional Cine Battery V-Mount Plate enables the use of V-Lock battery packs on cameras and/or numerous professional peripherals simultaneously. Featuring a high-quality aluminiumv-lock release, Hedbox UNIX plates are designed and tested for up to 10,000 battery cycles.

Three (3) D-Tap DC Power Outputs provide 14.8V/10A for extra devices and peripherals such as on-board recorders, LED lights, monitors, remote follow focus, wireless transmitters etc.

A built-in USB 5V / 2.1A Power Output is located on the top of the UNIX plate.

Designed with versatility in mind UNIX plates have multiple mounting holes to provide universal camera connection or peripheral mounting – 4x M3x12 screws are included with UNIX to mount the plate as required. The UNIX-1BL includes a hard-wired 50cm power cable with 2-pin Push Pull FHG.1B.302 Male Right Angle Connector that can be used to power various professional photo/video devices that accept FHG.1B.302 Connectors.

#### **FEATURES:**

#### Supplied Breakaway 50cm DC Cable with 2-pin Push Pull FHG.1B.302 Male Right Angle Connector

With an installed breakaway DC 14.8V/10A / 148W power cable, UNIX-1BL can be used to power Teradek products and various cameras and devices in the video and photo market. The breakaway cable is a 50cm long, with 2-pin Push Pull FHG.1B.302 Male Right Angle Connector included.

# **High Quality Aluminium V-lock release**

Adopting technology that allowed us to use a high-quality aluminum alloy V-lock release, the lock and unlock provides up to 10,000 cycles for a V-mount battery on the Unix plate.

#### 3 x D-Tap DC Power Output

Unix provides three D-Tap 14.8V / 10A DC power outputs. Three D-taps allow for extra powering for cameras, on board recorders, LED lights, monitors, remote follow focus, wireless transition systems, etc.

# Multiple Mounting holes for universal camera connection

With multiple mounting holes, (4 x M3x12 screws provided) Unix is able to mount on to any device or camera connection.

# Build-in USB 5V / 2.1A Power Out Socket

The USB 5V/2.1A output can be used to power any external USB electronic devices. This function allows you to use the Unix V-lock plate like a power station to charge your cell phone, tablet, or any other electronic devices that can be powered with USB 5V / 2.1A power.

#### **INCLUDED IN BOX:**

- 1 X UNIX-1BL V-MOUNT PLATE WITH BREAKAWAY 50CM CABLE 2-PIN PUSH PULL FHG.1B.302 MALE RIGHT ANGLE CONNECTOR
- 1 X SET SCREW M3X12 (4PCS)
- 1 X USER MANUAL (ENGLISH)
- 1 X 2 YEAR LIMITED MANUFACTURER'S WARRANTY

For more informations about our complete product range please visit our web site at www.hedbox.com



# **SPECIFICATION:**

Model:	UNIX-1BL V-Mount Adapter Power Plate
Battery Mount :	V-Lock Mount
D-Tap Power Out 1 :	DC 12V ~ 16.8V / 10A / 148W (Max) unregulated
D-Tap Power Out 2 :	DC 12V ~ 16.8V / 10A / 148W (Max) unregulated
D-Tap Power Out 3:	DC 12V ~ 16.8V / 10A / 148W (Max) unregulated
USB Output :	DC 5V / 2.1A /10W (Max)
Breakaway DC Cable :	DC 12V ~ 16.8V / 10A / 148W (Max) 50cm (length) 2-pin Push Pull FHG.1B.302 Male Right Angle Connector included
V-lock release :	High Quality <b>Aluminium</b> Alloy
Operating Temperature :	–20°C to +45°C (–4°F to +113°F)
Dimensions (WxDxH) :	146 x 102 x 26 mm
Weight:	~ 185 g
Mounting:	Multiple mounting holes for universal camera connection

